

Stainless Steel Pipe Size & Grade Standard

	Now Pine CD COLUMN COLUMN						
NB	Nom.Pipe	OD	SCH#10	SCH#40	SCH#80		
	SIZE	mm.	mm.	mm.	mm.		
	1/4"	13.72		2.24			
	3/8"	17.15		2.31			
15	1/2"	21.34	2.11	2.77	3.73		
20	3/4"	26.67	2.11	2.87	3.91		
25	1"	33.4	2.77	3.38	4.55		
32	1-1/4"	42.16	2.77	3.56	4.85		
40	1-1/2"	48.26	2.77	3.68	5.08		
50	2'	60.33	2.77	3.91	5.54		
65	2-1/2"	73.03	3.05	5.16	7.01		
65	2-1/2"	76.03	3.05	5.16	7.01		
80	3"	88.9	3.05	5.49	7.62		
100	4"	114.3	3.05	6.02	8.56		
125	5"	141.3	3.4	6.55	9.53		
150	6"	168.28	3.4	7.11	10.97		
200	8"	219.08	3.76	8.18	12.7		
250	10"	273.05	4.19	9.27	12.7		
300	12"	323.85	4.57	9.52	12.7		
350	14"	355.6	4.78	9.52			
400	16"	406.4	4.78	9.52			
450	18"	457.2	4.78	9.52			
500	20"	508	5.54	9.52			

^{*} Some grades are during the development process or under the testing process.



Welded Pipe

Welded steel pipe is manufactured by flat steel plate, with welding seam on the pipe body. Including ERW pipe, LSAW pipe, SSAW pipe.

It has the advantages of simple production process, high production efficiency, low cost, and fast development speed.

Seamless Pipe

Seamless steel pipe is manufactured by the round steel billet, through hot rolling, cold rolling or cold drawn processes, no seam on the pipe body.

It can improve the ability to withstand the pressure, has greater strength under load with uniformity of shape.

					11111	
SIZE	SPEC	OD	Т	Weight	SIZE	9
	3. 20	mm.	n. mm kg/pcs			
1/8"	#10	1.0.29	1.20	0.275	3-1/2"	
	#40	10.29	1.73	0.369	3 1/2	
1/4"	#10	13.72	1.65	0.464	4"	
1/4	#40	13.72	2.24	0.629	4	
2 /0"	#10	17.15	1.65	0.637	5"	
3/8"	#40	17.15	2.31	0.851		
1 /2"	#10	21.34	2.11	1.020	6"	
1/2"	#40	21.34	2.87	1.310		
2/4"	#10	26.67	2.77	1.300	8"	
3/4"	#40	26.67	2.38	1.740	· ·	
1"	#10	33.40	2.77	2.150	10"	
1"	#40	33.40	3.56	2.570	10	
1-1/4"	#10	42.16	2.77	2.760	12"	
	#40	42.16	3.56	3.470	12	
4.4./2.!!	#10	48.26	2.77	3.160	14"	
1-1/2"	#40	48.26	3.56	4.100	14	
2"	#10	60.33	2.77	3.980	16"	
2"	#40	60.33	3.91	5.440	16"	
2 1/2"	#10	76.30	3.05	5.420	18"	
2-1/2"	#40	76.30	5.2	9.120	10	
3"	#10	88.90	3.09	6.370	20"	
5	#40	88.90	5.49	11.300	20	

SIZE	SPEC	OD	Т	Weight		
3121	5	mm.	mm	kg/pcs		
3-1/2"	#10	101.50	3.05	7.29		
	#40	101.50	5.74	13.5		
4"	#10	114.30	3.05	8.23		
	#40	114.30	6.02	16.000		
5"	#10	139.80	3.40	11.400		
	#40	139.80	6.60	21.700		
6"	#10	165.20	3.40	13.600		
	#40	165.20	7.10	27.700		
8"	#10	216.30	4.00	20.900		
8"	#40	216.30	8.20	42.100		
10"	#10	267.40	4.00	26.000		
	#40	267.40	9.30	59.200		
12"	#10	318.40	4.50	34.800		
	#40	318.40	10.30	78.300		
14"	#10	355.60				
14"	#40	355.60	11.10	94.300		
16"	#10	406.40				
	#40	406.40	12.70	123.000		
18"	#10	457.20				
18	#40	457.20	14.3	156		
20"	#10	508.00				
20"	#40	508.00	15.1	184		

^{*} Some grades are during the development process or under the testing process.





SAMIL TECHNOLOGY (THAILAND) CO., LTD.

2/15 Moo.1T. Nongkham A. Sriracha Chonburi 20230

Tel. 038-480258 Fax. 038-480258 Email.samilaxon@gmail.com